

RECOMMENDED QUANTITY CHART FOR OFF THE ROAD TIRES					
2 GALLONS – 8 LITERS 12.00R24 13.00R24 14.00R24 16.00R24	3 GALLONS – 11 LITERS 18.00R25 21.00R25 20.5R25 23.5R25	4 GALLONS – 15 LITERS 18.00R33 21.00R35 18.00R49 21.00R49	5 GALLONS – 19 LITERS 24.00R35 33.5R33 29.5R35 33.25R35	8 GALLONS – 30 LITERS 45/65R45 27.00R49 30.00R51 30 R 56.5	15 GALLONS – 57 LITERS 37.00R57 42/90R57
14.00R25 16.00R25 15.5R25 17.5R25 14.9R24 16.9R24 17.5L R 24 19.5L R 24	5 29.5R25 29.5R29 16.9R28 33.25R29 18.4R28 23.1R26 21 L R 24 24.5R32	29.5R29 33.25R29 23.1R26	.5R29	10 GALLONS – 38 LITERS 33.00R51 36.00R51 37.5R51 50/65R51	20 GALLONS – 76 LITERS 40,00R57 46/90R57 48/95R57
			37.5R39 40.5R39 27 R 56.5		30 GALLONS – 114 LITERS ALL 63"

Judging the correct quantity

For bias ply off the road tires add 30% more **Tire Life®** than recommended above. Quantities provided above are taken from an average. Each operation is different. Only you can predict your needs accurately.

How to know you are right

When the proper quantity has been applied, your tires will dismount easily, rim rust will be eliminated, and the tire inner-liner will benefit from anti-oxidant protection.

Notes

- 1. For best use, you should make sure your wheels/rims and tires are well cleaned prior to installing Tire Life®. Tire Life® will clean rust and corrosion from your wheels/rims through the natural washing action created by a truck in motion. Tire Life® can be installed with an applicator tank into a mounted assembly without prior cleaning, but then should be checked or changed between 30 to 90 days.
- 2. A good rule of thumb for judging the correct amount of Tire Life® per tire: If you dismount the tire and have 50% or more of the original install amount left in the tire then you are within good operating tolerances for the effectiveness of Tire Life®.
- 3. Please contact your Fuller Brothers' Representative if you have any questions or if you would like an on-site assessment and follow up recommendations.

FULLER BROTHERS, INC. www.fullerbros.com

Corporate Head Office

P.O. Box 280 | 11507 S.E. Hwy 212, Clackamas, OR 97015 Main Line +1.503.657.9366 | Toll Free +1.800.547.7785

